


Connection of the OPMF options



The following figures show a brief overview of the connection of the OPMF options, which is also contained in the Options Manual (chapter 1.3.2).

1 Connection of the OPMF-8008-4A





* Option print, can be plugged on the standard board APCI-8008, extendible to 1 axis.
A total of 4 axes is available (3 axes on the standard board + 1 axis on the option print OPMF-8008-4A)

2 Connection of the OPMF-8008-5A





* Option print, can be plugged on the standard board APCI-8008, extendible to 2 axes.
A total of 5 axes is available (3 axes on the standard board + 2 axes on the option print OPMF-8008-5A)

3 Connection of the OPMF-8008-6A





* Option print, can be plugged on the standard board APCI-8008, extendible to 3 axes.
A total of 6 axes is available (3 axes on the standard board + 3 axes on the option print OPMF-8008-6A)

4 Connection of the OPMF-8008-7A



* Option print, can be plugged on the standard board APCI-8008, extendible to 4 axes.
A total of 7 axes is available (3 axes on the standard board + 4 axes on the option print OPMF-8008-7A)

5 Connection of the OPMF-8008-8A



* Option print, can be plugged on the standard board APCI-8008, extendible to 5 axes.
A total of 8 axes is available (3 axes on the standard board + 5 axes on the option print OPMF-8008-8A)