

Function Description

Counter/Timer

APCLe-1711, CPCIs-1711, APCI-1710 and CPCI-1710

Multifunction counter board, optically isolated



Product information

This manual contains the technical installation and important instructions for correct commissioning and usage, as well as production information according to the current state before printing. The content of this manual and the technical product data may be changed without prior notice. ADDI-DATA GmbH reserves the right to make changes to the technical data and the materials included herein.

Warranty and liability

The user is not authorised to make changes to the product beyond the intended use, or to interfere with the product in any other way.

ADDI-DATA shall not be liable for obvious printing and phrasing errors.

In addition, ADDI DATA, if legally permissible, shall not be liable for personal injury or damage to materials caused by improper installation and/or commissioning of the product by the user or improper use; for example, if the product is operated despite faulty safety and protection devices, or if notes in the operating instructions regarding transport, storage, installation, commissioning, operation, limit values, etc. are not taken into consideration.

Liability is further excluded if the operator changes the product or the source code files without authorisation and/or if the operator is guilty of not monitoring the permanent operational capability of working parts and this has led to damage.

Copyright

This manual, which is intended for the operator and its staff only, is protected by copyright.

Duplication of the information contained in the operating instructions and of any other product information, or disclosure of this information for use by third parties, is not permitted, unless this right has been granted by the product licence issued. Non-compliance with this could lead to civil and criminal proceedings.

ADDI-DATA software product licence

Please read this licence carefully before using the standard software! The customer is only granted the right to use this software if he/she agrees with the conditions of this licence.

The software may only be used to set up the ADDI-DATA products.

Reproduction of the software is forbidden (except for back-up and for exchange of faulty data carriers). Disassembly, decompilation, decryption and reverse engineering of the software are forbidden. This licence and the software may be transferred to a third party if this party has acquired a product by purchase, has agreed to all the conditions in this licence contract and the original owner does not keep any copies of the software.

Trademarks

- ADDI-DATA, APCI-1500, MSX-Box and MSX-E are registered trademarks of ADDI-DATA GmbH.
- Turbo Pascal, Delphi, Borland C, Borland C++ are registered trademarks of Borland Software Corporation.
- Microsoft .NET, Microsoft C, Visual C++, MS-DOS, Windows 7, Windows 10, Windows Server 2000, Windows Server 2003, Windows Embedded and Internet Explorer are registered trademarks of Microsoft Corporation.
- Linux is a registered trademark of Linus Torvalds.
- LabVIEW, LabWindows/CVI, DASyLab, DIAdem are registered trademarks of National Instruments Corporation.
- CompactPCI is a registered trademark of PCI Industrial Computer Manufacturers Group.
- VxWorks is a registered trademark of Wind River Systems, Inc.
- RTX is a registered trademark of IntervalZero.



Warning!

The following risks result from the improper implementation of the board and from use contrary to the regulations:



Personal injury



Damage to the board, the PC and peripherals



Pollution of the environment.

- Protect yourself, others and the environment!
- Read the safety precautions (yellow leaflet) carefully!
If this leaflet is not enclosed with the documentation, please contact us and ask for it.
- Observe the instructions of this manual!
Make sure that you do not forget or skip any step!
We are not liable for damages resulting from the wrong use of the board.
- Pay attention to the following symbols:



NOTICE!

Designates hints and other useful information.



NOTICE!

Designates a possibly dangerous situation.

If the instructions are ignored, the board, the PC and/or peripherals may be **destroyed**.



WARNING!

Designates a possibly dangerous situation.

If the instructions are ignored, the board, the PC and/or peripherals may be **destroyed** and persons may be **endangered**.

Contents

Warning!	3
Chapter overview	5
1 Function description	6
1.1 Board versions with "Counter/Timer" function	6
1.2 Block diagram	8
1.3 Used signals	9
1.4 Pin assignment: Function module	10
1.5 Connecting the signal generators	11
1.5.1 Connection to the screw terminal panel	11
1.6 Connection example	13
1.7 Mode description	13
1.8 Procedure for using the "Counter/Timer" function	14
2 Standard software	15
3 Appendix	16
3.1 Index	16
4 Contact and support	17

Figures

Fig. 1-1: Block diagram: "Counter/Timer" function	8
Fig. 1-2: Pin assignment: 50-pin D-Sub male connector (4 counter/timer modules)	10
Fig. 1-3: Pin assignment: 78-pin D-Sub female connector (APCLe-1711 and CPCIs-1711)	11
Fig. 1-4: Connection example: Function modules	13

Tables

Table 1-1: Board versions with "Counter/Timer" function	6
Table 1-2: Used signals	9
Table 1-3: Connection of the signal generators to the screw terminal panel	12

Chapter overview

In this manual, you will find the following information:

Chapter	Content
1	Function description including block diagram and pin assignment
2	Standard software: Information on the API software functions
3	Appendix with index
4	Contact and support address

This document solely describes the function "Counter/Timer".

For general information on the **APCLe-/CPCIs-1711** or **APCI-/CPCI-1710**, please read the respective Technical Description of these boards (see PDF links). It contains, for example, the chapter "Inserting and installing the board" that supports you in commissioning.

1 Function description

The “Counter/Timer” function is a programmable interval counter/timer, which is comparable to the Intel 82C54.

Each function module supports three individual 32-bit counters/timers, which can be read out or written on via the data bus, as well as a function and control logic.

Delay times are generated by the software control. It is possible for the user to program the desired delay time for the function module instead of setting time loops in the software. After the delay time has elapsed, an interrupt can be generated.

Features:

- 4 function modules with three 32-bit counters/timers each (only binary numbers)
- Optical isolation of the inputs and outputs through opto-couplers to prevent ground loops
- Processing of up to 5 MHz signals
- 6 programmable modes
- Status read-back and latch command
- Inputs and outputs invertible through software
- Hardware and software gates possible, can be read back
- Single interface: no multiple assignment of addresses
- Interrupt triggered by an individual release bit per counter/timer and an interrupt status register
- Available clock: PCI bus clock divided by 4 (only **APCI-1710**) or 10 MHz from the quartz oscillator on the board, can be selected through software

1.1 Board versions with “Counter/Timer” function



NOTICE!

With the 24 V version of the **APCI-1711**, **CPCI-1711** or **APCI-1710**, the “Counter/Timer” function can be used only to a limited extent.

Table 1-1: Board versions with “Counter/Timer” function

Board version	“Counter/Timer” function
APCI-1711	x
APCI-1711-24V	x*
APCI-1711-5V-I	x
CPCI-1711	x
CPCI-1711-24V	x*
CPCI-1711-5V-I	x


Board version	"Counter/Timer" function
APCI-1710	x
APCI-1710-24V	x*
APCI-1710-5V-I	x
APCI-1710-5V-I-O	x
CPCI-1710	x

* Pin Ax or Bx: Only a 24 V input is available, i.e., the output of counter/timer 0 or counter/timer 1 cannot be used.

The I/O specifications of the different board versions are available in the Technical Description of the **APCle-/CPCIs-1711** or **APCI-/CPCI-1710** (see PDF links).

1.2 Block diagram

Fig. 1-1: Block diagram: “Counter/Timer” function



1.3 Used signals

With each function module, the counter/timer function uses five inputs (C to G) and three outputs (A, B, H).

Table 1-2: Used signals

Signal name	Pin name	Signal type	Function
OUT0_x+/-	Ax+/-	Differential/TTL/ 24 V*	Output of counter/timer 0 (only input with 24 V*)
OUT1_x+/-	Bx+/-	Differential/TTL/ 24 V*	Output of counter/timer 1 (only input with 24 V*)
OUT2_x	Hx	24 V / optional 5 V	Output of counter/timer 2
GATE0_x	Ex	24 V / optional 5 V	Gate input of counter/timer 0
GATE1_x	Fx	24 V / optional 5 V	Gate input of counter/timer 1
GATE2_x	Gx	24 V / optional 5 V	Gate input of counter/timer 2
CLK0_x	-	-	Connected with internal clock (PCI bus clock divided by 4 (only APCI-/CPCI-1710) or 10 MHz)
CLK1_x+/-	Cx+/-	Differential/TTL/ optional 24 V	Clock/counter input of counter/timer 1
CLK2_x+/-	Dx+/-	Differential/TTL/ optional 24 V	Clock/counter input of counter/timer 2

x = Number of the function module (0-3)

* 24 V with 24 V board version

1.4 Pin assignment: Function module

Fig. 1-2: Pin assignment: 50-pin D-Sub male connector (4 counter/timer modules)

Pin			Pin					Pin		
34	+24 V / U _{Ref} *	Function module 2 (FM2)	18	FM2: OUT0_2+	34	18	1	GND	1	Function module 0 (FM0)
35	FM0: OUT2_0		19	FM2: OUT0_2-	35	19	2	FM0: OUT0_0+	2	
36	FM1: OUT2_1		20	FM2: OUT1_2+	36	20	3	FM0: OUT0_0-	3	
37	FM2: OUT2_2		21	FM2: OUT1_2-	37	21	4	FM0: OUT1_0+	4	
38	FM3: OUT2_3		22	FM2: CLK1_2+	38	22	5	FM0: OUT1_0-	5	
39	FM0: GATE0_0	Function module 3 (FM3)	23	FM2: CLK1_2-	39	23	6	FM0: CLK1_0+	6	Function module 1 (FM1)
40	FM1: GATE0_1		24	FM2: CLK2_2+	40	24	7	FM0: CLK1_0-	7	
41	FM2: GATE0_2		25	FM2: CLK2_2-	41	25	8	FM0: CLK2_0+	8	
42	FM3: GATE0_3		26	FM3: OUT0_3+	42	26	9	FM0: CLK2_0-	9	
43	FM0: GATE1_0		27	FM3: OUT0_3-	43	27	10	FM1: OUT0_1+	10	
44	FM1: GATE1_1		28	FM3: OUT1_3+	44	28	11	FM1: OUT0_1-	11	
45	FM2: GATE1_2		29	FM3: OUT1_3-	45	29	12	FM1: OUT1_1+	12	
46	FM3: GATE1_3		30	FM3: CLK1_3+	46	30	13	FM1: OUT1_1-	13	
47	FM0: GATE2_0		31	FM3: CLK1_3-	47	31	14	FM1: CLK1_1+	14	
48	FM1: GATE2_1		32	FM3: CLK2_3+	48	32	15	FM1: CLK1_1-	15	
49	FM2: GATE2_2	33	FM3: CLK2_3-	49	33	16	FM1: CLK2_1+	16		
50	FM3: GATE2_3			50	33	17	FM1: CLK2_1-	17		

* Pin 34: see Technical Description of the board

This pin assignment also applies to the **APCLe-1711** or **CPCIs-1711** if the cable **ST1711-50** is connected to the 78-pin D-Sub female connector of the board. For further information on this, please refer to the Technical Description of the **APCLe-1711** and **CPCIs-1711** (see PDF link).

Fig. 1-3: Pin assignment: 78-pin D-Sub female connector (APCLe-1711 and CPCIs-1711)

Pin		Pin		Pin		Pin	
78		59				39	20
77		58				38	19
76		57				37	18
75		56				36	17
74		55				35	16
73		54				34	15
72	+24 V / U _{Ref} *	53				33	14
71	FM3: OUT2_3	52	U _{Ref} *		GND	32	13
70	FM3: CLK2_3-	51	FM3: GATE2_3		FM3: GATE1_3	31	12
69	FM3: CLK2_3+	50	FM3: CLK1_3-		FM3: OUT1_3-	30	11
68	FM2: OUT2_2	49	FM3: CLK1_3+		FM3: OUT1_3+	29	10
67	FM2: CLK2_2-	48	FM2: GATE2_2		FM2: GATE1_2	28	9
66	FM2: CLK2_2+	47	FM2: CLK1_2-		FM2: OUT1_2-	27	8
65	FM1: OUT2_1	46	FM2: CLK1_2+		FM2: OUT1_2+	26	7
64	FM1: CLK2_1-	45	FM1: GATE2_1		FM1: GATE1_1	25	6
63	FM1: CLK2_1+	44	FM1: CLK1_1-		FM1: OUT1_1-	24	5
62	FM0: OUT2_0	43	FM1: CLK1_1+		FM1: OUT1_1+	23	4
61	FM0: CLK2_0-	42	FM0: GATE2_0		FM0: GATE1_0	22	3
60	FM0: CLK2_0+	41	FM0: CLK1_0-		FM0: OUT1_0-	21	2
		40	FM0: CLK1_0+		FM0: OUT1_0+		1

FM = Function module

* Pins 52 and 72: see Technical Description of the board

1.5 Connecting the signal generators

1.5.1 Connection to the screw terminal panel

On the screw terminal panel **PX8001**, the pins of the 50 pin D-Sub female connector and the terminals connected to them are numbered in the same way. Thus, the terminal assignment of the screw terminal panel is identical with the pin assignment of the 50-pin D-Sub male connector of the **APCI-/CPCI-1710** or with that of the 50-pin D-Sub male connector on the **ST1711-50** cable (**APCLe-/CPCIs-1711**).

The following table is to serve as a help for you when connecting the signal generators to the screw terminal panel. The blank fields in the "Signal generator" column can be filled in on the basis of the selected signal generator type.

Table 1-3: Connection of the signal generators to the screw terminal panel

Signal generator			Screw terminal panel PX8001 (50-pin)							
Pin No.	Pin name	Lead colour (cable)	Signal name	Terminal name	Signal type	Terminal No.				Terminal function
						FM0	FM1	FM2	FM3	
	+24 V / U _{Ref}		+24 V / U _{Ref}	+24 V / U _{Ref}	-	34	34	34	34	see Technical Description of the board
	GND		GND	GND	-	1	1	1	1	Ground
			OUT0_x+	Ax+	Diff./TTL/24 V*	2	10	18	26	Output of counter/timer 0 (only input with 24 V*)
			OUT0_x-	Ax-	Diff./TTL/24 V*	3	11	19	27	
			OUT1_x+	Bx+	Diff./TTL/24 V*	4	12	20	28	Output of counter/timer 1 (only input with 24 V*)
			OUT1_x-	Bx-	Diff./TTL/24 V*	5	13	21	29	
			CLK1_x+	Cx+	Diff./TTL/ optional 24 V	6	14	22	30	Clock/counter input of counter/timer 1
			CLK1_x-	Cx-		7	15	23	31	
			CLK2_x+	Dx+	Diff./TTL/ optional 24 V	8	16	24	32	Clock/counter input of counter/timer 2
			CLK2_x-	Dx-		9	17	25	33	
			GATE0_x	Ex	24 V / opt. 5 V	39	40	41	42	Gate input of counter/timer 0
			GATE1_x	Fx	24 V / opt. 5 V	43	44	45	46	Gate input of counter/timer 1
			GATE2_x	Gx	24 V / opt. 5 V	47	48	49	50	Gate input of counter/timer 2
			OUT2_x	Hx	24 V / opt. 5 V	35	36	37	38	Output of counter/timer 2
			CLK0_x	-	-	-	-	-	-	see Table 1-2
			-	-	-	-	-	-	-	-
			-	-	-	-	-	-	-	-


x = Number of the function module (0-3)

* 24 V with 24 V board version

1.6 Connection example

The counter/timer function is implemented on all function modules.

Fig. 1-4: Connection example: Function modules



1.7 Mode description

To program the individual counters/timers, six modes are available.

The counter/timer can be loaded with a new value and be read at any time. Before it is read though, the value has to be latched.

a) Mode 0: Interrupt at end of sequence

Mode 0 is used for counting events.

After the initialisation, the output is set to "Low". When the counter has reached the value 0, the output is set to "High". It keeps this position until a new counting sequence starts or a new counter value is written.

b) Mode 1: Hardware-retriggerable monoflop

In this mode, the GATE input is used to trigger the timer instead of activating or deactivating it. Except for this, this mode corresponds to Mode 0.

c) Mode 2: Pulse generator

In this mode, the counter divides the selected input clock by the start value "ul_ReloadValue". Mode 2 is suited to generate a real-time clock interrupt.

After the initialisation, the output is set to "High". When the counter has reached the value 1, the output is set to "Low". After just one clock pulse, it is reset to "High". The counter reloads the start value ("ul_ReloadValue") and the counting sequence is rerun. The number of sequences is infinite. An interrupt can always be generated at the end of a sequence.

Time computation: $(ul_ReloadValue + 2) \times input\ clock$

d) Mode 3: Square wave signal generator

In Mode 3, the baud rate is generated. This mode differs from Mode 2 only as far as the output sequence is concerned.

After the initialisation, the output is set to "High". When the counter has run down to the half of the start value, the output is set to "Low". It keeps this position until a new counting sequence starts. The number of sequences is infinite.

Time computation: $(ul_ReloadValue + 2) \times input\ clock$

e) Mode 4: Software-triggered strobe

After the initialisation, the output is set to "High". When the counter has run down, the output is set to "Low". After just one clock pulse, it is reset to "High".

The counting sequence is triggered by writing the start value. If a new value is written during the counting sequence, this value is loaded as the new start value at the next clock pulse.

f) Mode 5: Hardware-triggered strobe (retriggerable)

In this mode, the GATE input is used to trigger the timer instead of activating or deactivating it. Except for this, this mode corresponds to Mode 4.

1.8 Procedure for using the "Counter/Timer" function

In order to use the "Counter/Timer" function, the following steps need to be performed:

- 1.** Program the counter/timer in the desired mode.
- 2.** Adapt the signals GATE or OUT to the desired level.
- 3.** Write the reload value to the timer.

The counter/timer is now ready for use.

If you want to use the interrupt function, you first have to set the release bits for the interrupt to "1".

2 Standard software

The API software functions supported by the board are listed in an HTML document. A description of how to access the respective file can be found in the document "Quick installation PC boards" (see PDF link), in the chapter "Standard software".

3 Appendix

3.1 Index

Block diagram 8
Board versions 6
Connection
 Signal generators 11
Connection example 13

Modes 13
Pin assignment 10
Signals 9
Standard software 15

4 Contact and support

Do you have any questions? Write or call us:

Address: ADDI-DATA GmbH
Airpark Business Center
Airport Boulevard B210
77836 Rheinmünster
Germany

Phone: +49 7229 1847-0

Fax: +49 7229 1847-222

E-mail: info@addi-data.com

Manual and software download from the Internet:

<https://drivers.addi-data.com>